



BAMBI

code 2900

Specifications

Bambi 100W - 12V

kg. 0,570 (with cable)
with handgrip and integral camera shoe/stand mount

Lightweight construction in aluminum.

Front radiator for excellent cooling.

Spot/flood rear knob.

Integral safety glass.

Extra-pure polished aluminium reflector.

On board switch 6A.

Epoxy anti-scratch finish.

Lamp type FCR 100W 12V (3200°k) Lampholder: G 6,35.

Power cable 1,50m. long -Sez. 2 x 1,5 mmq with XLR4 connector

Compact size: lamphead height 119mm, length 79mm, width 143,5mm - handle: 114mm



Accessories

Code 2901: 110 gr. Four leaf barndoor + gel clips

Code 2902: 90 gr. Diffuser glass

Code 1705: Short camera mount

Code 106: Mini Pro Alu stand (Minipro 051N)

Code C60 H1209: Combi Pack 12V 9.5Ah Ni-Mh

Code C60 LG 120: Charger for Combi Pack

Code C60 H1208: Battery belt 12V 8.5Ah Ni-MH with internal charger

Photometrics

DISTANCE 2 m (LAMP TYPE 100W 12V 64625)	SPOT	FLOOD
light center value	1850	310
beam angle= beam at 50% peak value	22°	59°
field angle= beam at 10% peak value	43°	106°
RATIO	1:5,97	



Battery belt

12V 8.5Ah Ni-Mh **Code C60 H 1208**



WITH INTERNAL CHARGER

weight: 2,7kg
size: 60*13*5cm
charging time: 4,5h
runtime 12V 100W: 66min
Service Life: >500 cycles
Input Voltage: 90-250VAC
Input Power: 45W

Combi Pack

12V 9,5Ah Ni-Mh **Code C60 H 1209**



weight: 2 kg
size: 21x14x50mm
charging time: 4,5h
duration 12V 100W: 70min
with XLR4

Charger

Code C60 LG 120



CHARGER FOR COMBI PACK