



## Specifications

**Minirama** fixtures are the ideal solution for lighting evenly cycloramas and backgrounds.

**Minirama** can be used in a wide range of combinations from single-cell unit up to 4-cell fixture, so as to may obtain a more powerful illumination and more chromatic effects.

**Minirama** can be also used as groundrow unit.

**Minirama** cells fit 625W, 1000W and 1250W quartz-halogen bulbs, R7s based and 190mm long.

Construction: steel housing

Finish: Heat resistant matt black

Mirror: Soft-reflection aluminium finish

Lampholder: R7s

Stirrup: Manual and Pole operated

Power cable: CEI 20-22, 1 m long - section 3x1,5mmq

Weight: 3,2 kg. - single unit (M.O.); 6,3 kg. - single unit (P.O.)



## Photometrics

**MINIRAMA 1250W** positioned downward (inclination  $10^{\circ}/11^{\circ}$ ) at 2,85m from a background high 7,5m, offers an illumination range of 1000Lx (top) - 230Lx (ground).  
Ideal distance of Miniramas in a downward row is 2,5m (centre-centre).

If positioned upward in the same conditions, the illumination ranges from 1150Lx (top) to 320Lx (ground).  
Ideal distance of Miniramas in an upward row is 2m (centre-centre).