



Specifications

Lightweight and rugged aluminium construction.

Housing designed like a radiator for excellent cooling.

For G4 based halogen bulbs 20W, 30W, 35W/6V (Divino 1950) or 20W 12V (Divino 1960).

Fitted with power cable and jack connector 2.1mm with locking screw for Laniro Pocket

Battery system (available with other connectors on demand).

Divino 6V system consists of:

- DIVINO lamphead **Code 1950**
- Barndoor/Flip at daylight filter **Code 1951**
- Pocket Battery NiMH 6V **Code 1952**
- Quick Charger 6V **Code 1953**

Divino 12V system consists of:

- DIVINO lamphead **Code 1960**
- Barndoor/Flip at daylight filter **Code 1951**
- Pocket Battery NiMH 12V **Code 1924**
- Quick Charger 12V **Code 1925**

Pocket Battery 6V High Power NiMH 4.1Ah **Code 1952**

Specifications

Type: 5 NiMH cells in black pouch with adjustable belt

Volts: 1,2V per cell

Nominal capacity: 4100mAh

Max discharge range: from 410mA to 12300mA

Cycles: 500 cycles (Standard IEC)

Weight: 290 gr.

LAMP	DURATION	CONSUMPTION
20W	1h20'	3.3A
35W	0h55'	5.0A
50W	0h45'	5.8A





Pocket Battery 6V High power Ni-Mh 8.2Ah Code 1956

Specifications

Type: 10 NiMH cells in black leather pouch with adjustable belt

Volts: 1,2V per cell

Nominal capacity: 4100mAh

Max discharge range: from 410mA to 12300mA

Cycles: 500 cycles (Standard IEC)

Weight: 580 gr.

LAMP	DURATION	CONSUMPTION
20W	2h40'	3.3A
35W	1h50'	5.0A
50W	1h30'	5.8A

charging time with charger 1953 5 hours

Quick charger Code 1953

Quick charger for Pocket Battery ref. 1952 & Pocket Battery ref. 1956

Specifications

Type: switching - 90-264V AC/50 - 60Hz

Providing protection against overheating and overcharging.

It can charge 4-6 Ni-CD or NiMH cells from 4.8V to 7,2V

Weight: 286 gr.

Pocket Battery 12V High power Ni-Mh 4.1Ah Code 1924

Specifications

Type: 10 NiMH cells in black leather pouch with adjustable belt

Volts: 1,2V per cell

Nominal capacity: 4100mAh

Max discharge range: from 410mA to 12300mA

Cycles: 500 cycles (Standard IEC)

Weight: 580 gr.

Measures: height 115mm, length 77mm, width 47mm

LAMP	DURATION	CONSUMPTION
20W	2h20'	1.6A

charging time with charger 1925 5 hours

Quick charger Code 1925

Quick charger for Pocket Battery ref. 1924

Specifications

Type: switching - 90-264V AC/50 - 60Hz

Providing protection against overheating and overcharging.

It can charge 10-12 Ni-CD or NiMH cells from 12V to 14V

Weight: 286 gr.

Photometrics

DISTANCE 1 m (LAMP TYPE 20W 6V 7388)	SPOT	FLOOD
light center value	565	342
beam angle	21°	41°
RATIO	1: 1,65	

