



Specifications

Category : **ENG**

Application : **hand held lamphead for reportage with digital camcorders**

(75w-100w 12v suitable to hand held lightings with: DVW790WSP, DVW709WSP, PDW510P, PDW530P ; DY700E, DY90WE, AJ-D410/610, P2)

Industry leading power to rate ratio, focusable and robust. Ideal for shootings on location when the ENG set area requires more light than normally available from on board lights. As the HDV and DV Cam_lights, it is designed to offer variable focus, great efficiency, high quality illumination.

Supplied fully equipped in Set READY TO GO.

(diffuser, daylight filter, barndoor and lamp included in the price)

- Superior quality german reflector materials 99,99% extra pure.
- Computer aided parabolic design & reflector coatings (by proprietary laniro software).
- Robust and durable construction.
- Wide beam apertures. Variable spot-flood.
- Professional design.
- Handle integrating the camera and stand mount.

Photometrics

DISTANCE 2 m (LAMP TYPE 100W 12V 64625)	SPOT	FLOOD
light center value	1850	310
beam angle= beam at 50% peak value	22°	59°
field angle= beam at 10% peak value	43°	106°
RATIO	1:5,97	



ACCESSORIES SET INCLUDED



C60 CP1205 COMBI PACK 12V 9,5AH NiMH



C60 LG120 CHARGER FOR COMBI PACK