

GULLIVER 300W



code 1760

Specifications

Gulliver 30: 300w - 120/240V

yoke mount - kg.0,650

with dimmer: **code 1760 dim**

Lightweight construction in aluminum.

Front radiator housing.

Spot/flood by rear knob.

Integral safety glass.

Switch 6Amp. 230V - 8Amp. 24V placed on the rear panel.

Extra-pure polished aluminium reflector.

Epoxy anti-scratch finish.

Lamp type 64516 osram (300w - 3200°k) 230v

Lampholder: G 6,35.

Power cable 3,50m. long, section 3 x 0,75 mmq.

Available in-line dimmer 60-300W 230V AC, 50Hz.



Accessories

Code 1701: 110 gr. Four leaf barndoor + gel clips

Code 1702: 90 gr. Dichroic daylight filter

Code 1703: 90 gr. Diffuser glass

Code 1705: Short camera mount

Code PHO WD small: White dome

Code 161: 320 gr. Umbrella ø 80 cm.

Code M026: 350 gr. Umbrella universal adapter lite-tite

Code 106: Mini Pro Alu stand (Minipro 051N)

Code 301: Maxi Alu stand (compact 052)

Code 327: Gag grip with 5/8" (16mm) spigot

Photometrics

	DISTANCE 1m		DISTANCE 2m		DISTANCE 3m	
	SPOT	FLOOD	SPOT	FLOOD	SPOT	FLOOD
Øbeam	60	80	1,20	1,70	1,80	2,50
LUX	9860	5000	2640	1320	1190	680

Fitting halogen lamps with G 6,35 (bi-pin)base 3200°K



CODE 1760 with dimmer