



ICE2

IANIRO COOL EQUIPMENT

ICE2: 125W Weight 6.5 kg
Candelas 3,800 Lamp 2x PL-L 55 W



Dimming Options

Code 70165 Non-Dim models are "switch-on/switch-off", so cannot be dimmed and must be used on a non-controlled A/C line.

Code 70166 Basic models are dimmed by turning a potentiometer at the back of the unit. They must be used on a non-controlled A/C line.

Code 70167 DMX models have a built-in DMX receiver which is set at any address between 1 and 512. They are dimmed by the DMX console. They must be used on a non-controlled A/C line.

Code 70168 Phase models are connected to a controlled A/C line (triac or thyristor dimmer) and can only be dimmed by such an external dimmer.

Accessories

Code 70264 Grid spot 40°

Code 70266 Grid spot 60°

Code 70526 Pole operated yoke mount

Code 70526 UPG pole operated upgrade

Code 70460 Filter holder

Code 70360 Diffuser

Photometrics

MODEL	POWER	# LAMPS	CANDELAS	ANGLE	WORKING DISTANCE	2m	3m	4m	5m	6m
ICE2	125W	2	3,800	55°	2 to 3 m (6 to 10 ft)	950	425	240	-	-

NOTE: light levels for Philips lamps. Increase specifications by 15% for Osram Studioline ratings. Lower specifications by 25% for Osram Dulux ratings.

