



ICE4

IANIRO COOL EQUIPMENT

ICE4: 250W Weight 10 kg
Candelas 8,300 Lamp 4x PL-L 55 W



Dimming Options

Code 70175 Non-Dim models are "switch-on/switch-off", so cannot be dimmed and must be used on a non-controlled A/C line.

Code 70176 Basic models are dimmed by turning a potentiometer at the back of the unit. They must be used on a non-controlled A/C line.

Code 70177 DMX models have a built-in DMX receiver which is set at any address between 1 and 512. They are dimmed by the DMX console. They must be used on a non-controlled A/C line.

Code 70178 Phase models are connected to a controlled A/C line (triac or thyristor dimmer) and can only be dimmed by such an external dimmer.

Accessories

Code 70274 Grid spot 40°

Code 70276 Grid spot 60°

Code 70576 Pole operated yoke mount

Code 70576 UPG pole operated upgrade

Code 70470 Filter holder

Code 70370 Diffuser

Photometrics

MODEL	POWER	# LAMPS	CANDELAS	ANGLE	WORKING DISTANCE	2m	3m	4m	5m	6m
ICE4	250W	4	8,300	55°	3 to 4 m (10 to 13 ft)	2075	925	520	-	-

NOTE: light levels for Philips lamps. Increase specifications by 15% for Osram Studioline ratings. Lower specifications by 25% for Osram Dulux ratings.

