



ICE6

IANIRO COOL EQUIPMENT

ICE6 :375W Weight 15 kg
Candelas 13,500 Lamp 6x PL-L 55 W



Dimming Options

Code 70185 Non-Dim models are "switch-on/switch-off", so cannot be dimmed and must be used on a non-controlled A/C line.

Code 70186 Basic models are dimmed by turning a potentiometer at the back of the unit. They must be used on a non-controlled A/C line.

Code 70187 DMX models have a built-in DMX receiver which is set at any address between 1 and 512. They are dimmed by the DMX console. They must be used on a non-controlled A/C line.

Code 70188 Phase models are connected to a controlled A/C line (triac or thyristor dimmer) and can only be dimmed by such an external dimmer.

Accessories

- Code 70284** Grid spot 40°
- Code 70286** Grid spot 60°
- Code 70586** Pole operated yoke mount
- Code 70586** UPG pole operated upgrade
- Code 70480** Filter holder
- Code 70380** Diffuser

Photometrics

MODEL	POWER	# LAMPS	CANDELAS	ANGLE	WORKING DISTANCE	2m	3m	4m	5m	6m
ICE6	375W	6	13,500	55°	4 to 5 m (13 to 16 ft)	3375	1500	845	540	375

NOTE: light levels for Philips lamps. Increase specifications by 15% for Osram Studioline ratings. Lower specifications by 25% for Osram Dulux ratings.

