



**ICE8**: 500W Weight 19 kg  
Candelas 17,500 Lamp 8x PL-L 55 W



### Dimming Options

**Code 70195 Non-Dim** models are "switch-on/switch-off", so cannot be dimmed and must be used on a non-controlled A/C line.

**Code 70196 Basic** models are dimmed by turning a potentiometer at the back of the unit. They must be used on a non-controlled A/C line.

**Code 70197 DMX** models have a built-in DMX receiver which is set at any address between 1 and 512. They are dimmed by the DMX console. They must be used on a non-controlled A/C line.

**Code 70198 Phase** models are connected to a controlled A/C line (triac or thyristor dimmer) and can only be dimmed by such an external dimmer.

### Accessories

**Code 70294** Grid spot 40°

**Code 70296** Grid spot 60°

**Code 70596** Pole operated yoke mount

**Code 70596** UPG pole operated upgrade

**Code 70490** Filter holder

**Code 70390** Diffuser

### Photometrics

MODEL	POWER	# LAMPS	CANDELAS	ANGLE	WORKING DISTANCE	2m	3m	4m	5m	6m
<b>ICE8</b>	500W	8	17,500	55°	5 to 8 m (16 to 25 ft)	4375	1945	1095	700	485

NOTE: light levels for Philips lamps. Increase specifications by 15% for Osram Studioline ratings. Lower specifications by 25% for Osram Dulux ratings.

