

# PHOTOFLOOD/MINIPINZA



code I15/100

## Specifications

### Photoflood I15 500W - 120/240V

Clamp + jointed arm mount

kg. 1,170

### Minipinza 100 250W - 120/240V

Clamp + jointed arm mount

kg. 1,140

Aluminum housing.

Epoxy anti-scratch red finish: black and silver colour on request.

Aluminium finish on the inside.

Lampholder E 27.

Protective lampholder housing in fibre glass.

Black fibre glass clamp with flexible arm.

Power cable 3,50 m. long, section 3x1,5 mm<sup>2</sup>. CEI 20-22

In-line switch 8Amp 250V.

### For architectural applications

fitting long life halogen lamps type E27 250w type 64480



## Accessories

### Photoflood:

**Code 802:** 380 gr. Four leaf barndoor with gel clips.

**Code 801:** 435 gr. Four leaf barndoor/wire guard assembly with gel clips.

**Code 807:** 290 gr. Snoot ø 85 mm - 245mm long

**Code 806:** 240 gr. Snoot ø 134 mm - 132mm long

### Minipinza:

**Code 159:** 215 gr. Four leaf barndoor with gel clips.  
(It can fit the accessories line of Lilliput.)

## Photometrics

DISTANCE 3 m (500w - argaphoto PF318)	
light center value	302
beam angle= beam at 50% peak value	98°
field angle= beam at 10% peak value	137°

Fitting incandescent lamps with E27 base type PF318 3200°K

