

MINISPOT

code 1200



Specifications

Construction: cast aluminum.
Heat resistant matt black finish.
Fresnel lens Ø 80 mm. (3 1/4") F 50
Extra-pure polished aluminum reflector.
Lampholder GY 9,5.
Fitting lamps 300w CP81 e 500w CP82 (3200°k)
Spot-flood rear knob.
Aluminum yoke with 5/8" (16 mm.) socket.
Power cable 3,50m. long, section 3x1,5mm². CEI 20-22.
In-line switch 8 Amp. 250V (16 Amp. 125V).
Available with dimmer in-line.(60-500W 230V AC, 50Hz)
Supplied with integral wire guard.
Weight 2,150 kg. (without accessories).

Accessories

Code 1206: 30 gr. Wire guard.
Code 1201: 280 gr. Four leaf barndoor + gel clips.
Code 1202: 50 gr. Gel frame.
Code 1207: 25 gr Double scrim.
Code 1208: 20 gr. Single scrim.
Code 1209: Halfsingle scrim
Code 1210: Halfdouble scrim
Code 1203: 280 gr. Cone variable front diameter 30-50-70 mm.
Code 1205: 50 gr. Table stand with 5/8" (16 mm.) spigot.
Code 106: Mini Pro Alu stand (Minipro 051N)
Code 301: Maxi Alu stand (compact 052)
Code 327: Gag grip with 5/8" (16mm) spigot

Photometrics

DISTANCE 5 m (2000w)	SPOT		FLOOD	
	CP81	CP82	CP81	CP82
light center value	2220	2860	490	998
beam angle= beam at 50% peak value	12°30'	15°30'	46°	44°
field angle= beam at 10% peak value	22°40'	27°40'	62°45'	58°40'
RATIO	1:4.5 (CP81) 1:2.87(CP82)			

Fitting halogen lamps with GY9,5 base

