



### Specifications

**Varibeam code 180** 800W - **code 200** 1000W - 120/240V

yoke mount  
kg.1,63

Extra-pure polished aluminium reflector.

Inside cup matt black finished

Lampholder type R7s.

Spot-flood rear knob.

Power cable 3,50 m. long, section 3x1,5 mm.2 CEI 20-22.

In-line switch 8 Amp. 250V (16 Amp. 125V) with fibre glass protective housing.

Yoke mount in aluminium with 5/8" (16mm) socket

### Accessories

**Code 118:** CE 200 gr. Wire guard with holder ring for barndoors and other accessories. Integrated to CE fixtures.

**Code 802:** 380 gr. Four leaf barndoor + gel clips

**Code 801:** 435 gr. Four leaf barndoor/wire guard assembly + gel clips

**Code 183:** 440 gr. Accessory holder

Accessories to be fitted in accessory holder 183:

**Code 195:** 20 gr. Wire guard

**Code 803:** 180 gr. Safety glass

**Code 805:** 180 gr. Diffuser glass

**Code 184:** 180 gr. Dichroic daylight filter

**Code 185:** 25 gr. Double scrim

**Code 186:** 20 gr. Single scrim

**Code 187:** 20 gr. Half double scrim

**Code 189:** 30 gr. Half single scrim

**Code PHO WD:** Medium White dome

**Code 182:** 550 gr. Umbrella diam. 100

**Code M026:** 350 gr. Umbrella universal adapter lite-tite

**Code 301:** Maxi Alu stand (compact 052)

**Code 106:** Mini Pro Alu stand (Minipro 051N)

**Code 327:** Gag grip with 5/8" (16mm) spigot



### Photometrics

DISTANCE 5 m (800w DXX)	SPOT	FLOOD
light center value	1235	445
beam angle= beam at 50% peak value	36°30'	69°
field angle= beam at 10% peak value	90°	129°
RATIO	1:2.78	

Fitting halogen lamps with R7s base.

Long 80mm: 800w P2/13 DXX - 600w L598 - 500w L600

Long 93mm: 1000w P2/35 13704 - 800w L603 - 600w L604